

Semi-recessed ceiling and wall luminaire · Opal glass · Tunable white

**BEGA**

**Application**

This unique, slightly convex opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly with tunable white technology. The lateral illumination on the finished surface produces a floating effect.

**Materials**

Hand-blown opal glass  
 Aluminum housing  
 Stainless steel screw clamps  
 Aluminum ceiling mounted driver box

**NRTL** listed to North American Standards, for interior use only

**Weight:** 1.8 lbs.

**Electrical**


Operating voltage 120-277VAC  
 Minimum start temperature -20° C  
 LED module wattage 28.1 W  
 System wattage 33.0 W  
 Controllability DALI  
 Color rendering index Ra > 90  
 Luminaire lumens 1986 lm  
 LED service life (L70) 60000 hrs

**Dynamic range**

Tunable white color temperature range is adjustable from 2700K to 6500K

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:  
 BEGA Product:  
 Project:  
 Modified:



Semi-recessed ceiling and wall luminaire · Opal glass · Tunable white

	LED	A	B	C
<b>B50204</b>	28.1 W	14 <sup>7</sup> / <sub>8</sub>	2 <sup>3</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>2</sub>

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

