

Application

Semi-recessed downlight with tunable white technology. A crystal glass optical lens refracts the powerful LED output, collimating the center portion within the reflector for the downlight component. At the same time, a portion of the light is refracted outward to illuminate the external three-ply opal glass. This creates vertical illuminance and adds an artistic touch to a typical downlight.

Materials

- Hand-blown three-ply opal glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box
- Pure anodized aluminum reflector

NRTL listed to North American Standards, for interior use only

Weight: 3.9 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	21.4 W
System wattage	24.9 W
Controllability	DALI
Color rendering index	Ra > 90
Luminaire lumens	1645 lm
LED service life (L70)	60000 hrs

Dynamic range

Tunable white color temperature range is adjustable from 2700K to 6500K
BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Polished aluminum (.3)
- Stainless steel (.2)

Type:
BEGA Product:
Project:
Modified:

Available options
CP50267 Ceiling pan (DALI-2 controlled only)



Semi-recessed downlight · Opal glass · Tunable white						
	LED	□	A	B	C	D
B50267	21.4 W	47°	7 1/2	3 3/4	1 3/4	8 1/2

