

Semi-recessed ceiling luminaire · Opal glass • Tunable white

BEGA

Application

Semi-recessed luminaire with hand-blown, three-ply opal glass with a distinctive form and tunable white technology. This unshielded, semi-recessed luminaire with wide beam distribution is characterized by a very shallow height and compact dimensions. A diffuse lens with concave interior creates a smooth light gradient across the satin matte glass.

Materials

Hand-blown three-ply opal glass
 Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Stainless steel screw clamps
 Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 4.0 lbs.


Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	21.4 W
System wattage	27.0 W
Controllability	DALI
Color rendering index	Ra > 90
Luminaire lumens	1488 lm
LED service life (L70)	60000 hrs

Dynamic range

Tunable white color temperature range is adjustable from 2700K to 6500K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details



Semi-recessed ceiling luminaire · Opal glass • Tunable white

	LED	A	B	C
B50271	21.4 W	8 ⁷ / ₈	2 ⁵ / ₈	1 ³ / ₄

Type:

BEGA Product:

Project:

Modified:

Available options

CP50267 Ceiling pan (DALI-2 controlled only)



BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
 © copyright BEGA 2024 Updated 01/22/24