

Semi-recessed ceiling and wall luminaire · Opal glass • Tunable white

BEGA

Application

Hand-blown, three-ply opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly with tunable white technology. The lateral illumination on the finished surface produces a floating effect.

Materials

Hand-blown opal glass
 Aluminum housing
 Stainless steel screw clamps
 Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 6.8 lbs.

Electrical


Operating voltage 120-277VAC
 Minimum start temperature -20° C
 LED module wattage 28.1 W
 System wattage 33.0 W
 Controllability DALI
 Color rendering index Ra > 90
 Luminaire lumens 2121 lm
 LED service life (L70) 60000 hrs

Dynamic range

Tunable white color temperature range is adjustable from 2700K to 6500K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
 BEGA Product:
 Project:
 Modified:



Semi-recessed ceiling and wall luminaire · Opal glass • Tunable white

		LED	A	B
B50295	ADA	28.1 W	13 1/2	2 3/8



BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com