Application

Recessed ceiling luminaire designed with an efficient hybrid optical system that makes use of a silicone optical lens and precise reflector for maximum glare suppression. Designed for trimless installations, this luminaire provides a very clean ceiling appearance.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Composite installation housing

Pure anodized aluminum reflector surface

Silicone optic with excellent high temperature and UV stability

BEGA Hybrid Optics®

NRTL listed to North American Standards, for interior use only

Weight: 3.1 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -20° C
LED module wattage 14.9 W
System wattage 21.0 W

Controllability 0-10V dimming down to 0.1%

Color rendering index Ra > 90 Luminaire lumens 2201 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


White finish. Custom colors not available.

Type:

BEGA Product:

Project: Modified:





| Recessed downlight · Very wide beam | | | | | |
|-------------------------------------|-------|-----|------|------|--|
| | LED | | А | В | |
| B50385 | 14.9W | 59° | 63/4 | 47/。 | |