

Application

A round in-grade intended for the illumination of walls, foliage, and architectural features. Designed to bear pressure loads up to 11,000 lbs. from vehicles with pneumatic tires. The luminaire must not be used for traffic lanes where it is subject to horizontal pressure from vehicles braking, accelerating, or changing direction.

Materials

- Clear safety glass
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Corrosion-resistant 304 grade stainless steel
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Fully potted waterstopper cable
- High temperature silicone gasket
- Stainless steel screw clamps
- Mechanically captive stainless steel fasteners
- BEGA Hybrid Optics®
- Composite concentric ring louver
- Pure anodized aluminum reflector surface
- Silicone optic with excellent high temperature and UV stability

Weight: 11.9lbs.

Mounting

Aluminum installation housing

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	17.7 W
System wattage	21.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	2127 lm
LED service life (L70)	60000 hrs

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Metal Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:


Modified:

Available options

B10014	Elliptical spread lens
B71215	Concentric ring louver
DALI-2	DALI dimming
FSC	Fusing
NSL	Non-skid lens

Included (available for pre-shipment)

BB84289	Installation housing
---------	----------------------



In-grade luminaire · Adjustable · Wide beam

	LED	β	A	B	C
B84896	17.7 W	21°	8 1/8	9 7/8	8 1/2

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of our products and the associated technologies, data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please consult factory.
© copyright BEGA 2024

Updated 04/14/24