

Application

Compact ceiling and wall luminaire with unshielded light. Elegant luminaire housing without any visible fasteners. A die-cast aluminum housing and thick-walled crystal glass combined with LED technology makes this luminaire a durable and cost-effective solution for interior spaces.

Materials

Pressed crystal glass with white ceramic coating on one side
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, for interior use only

Weight: 2.1 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	4.1 W
System wattage	7.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	379 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Chrome (.3)
- Stainless steel (.2)



Ceiling and wall luminaire · Crystal glass

		LED	A	B
B50535	ADA	4.1 W	6 ¹ / ₄	2 ⁵ / ₈

Type:
 BEGA Product:
 Project:
 Modified:

