

Application

Compact ceiling and wall luminaire with unshielded light. Elegant luminaire housing without any visible fasteners. A die-cast aluminum housing and thick-walled crystal glass combined with LED technology makes this luminaire a durable and cost-effective solution for interior spaces.

Materials

Pressed crystal glass with white ceramic coating on one side
Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, for interior use only

Weight: 6.4 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20°C
LED module wattage	15.2W
System wattage	19.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	1461 lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1) Stainless steel (.2)
Chrome (.3)



Ceiling and wall luminaire · Crystal glass

		LED	A	B
B50537	ADA	15.2 W	10 ¹ / ₄	3 ¹ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2024 Updated 05/05/23