

Application

The thick-walled crystal glass of this downlight brings sparkle and added interest to any ceiling surface, while the inner frosted section provides glare control and minimizes the direct view of the LED source. The compact, shallow housing is ideal for areas with low ceiling heights such as lobbies and corridors.

Materials

Partially frosted pressed crystal glass
 Aluminum housing
 Galvanized zinc-plated mounting bracket
 Pure anodized aluminum reflector surface

NRTL listed to North American Standards, for interior use only

Weight: 4.9 lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -30° C
 LED module wattage 17.0W
 System wattage 20.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 90
 Luminaire lumens 2113lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)

Type:
 BEGA Product:
 Project:
 Modified:



Ceiling luminaire · Crystal glass

	LED	A	B
B50570	17.0W	7	3 ³ / ₄

