

Application

This recessed downlight's unique beauty and versatility is enhanced by the choice of four matte interior finishes combined with a white trim finish. These finishes may be chosen to complement a wide array of interior spaces. A subtle hint of colored light on the outside edge of the beam spread results from the internally reflected light. The result is an eye-catching and elegant lighting effect.

Materials

Clear UV-stabilized acrylic diffuser
 Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 1.0 lbs.

Electrical

| | |
|---------------------------|----------------------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -20° C |
| LED module wattage | 10.0 W |
| System wattage | 12.0 W |
| Controllability | 0-10V dimming down to 0.1% |
| Color rendering index | Ra > 90 |
| Luminaire lumens | 757 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired interior finish by using appropriate code number as suffix.

Available colors

- | | |
|------------------|---------------------|
| White (.1) | Matte aluminum (.2) |
| Matte brass (.4) | Matte copper (.6) |



| Downlight · STUDIO LINE · White | | | | |
|---------------------------------|-------|-----|--------|----|
| | LED | □ | A | B |
| B50578 | 10.0W | 65° | 5 1/8" | 3" |

Type:
 BEGA Product:
 Project:
 Modified:

