

Application

This pendant features thick-walled crystal glass, adding sparkle and visual interest to a room while the inner frosted section provides glare control and minimizes direct view of the LED source.

Materials

Partially frosted pressed crystal glass
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Galvanized zinc-plated mounting bracket
 Pure anodized aluminum reflector surface
 Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 3.1 lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -20° C
 LED module wattage 8.1 W
 System wattage 11.0 W
 Controllability 0-10V dimming down to 0.1%
 Color rendering index Ra > 90
 Luminaire lumens 858 lm
 LED service life (L70) 60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)



Pendant luminaire · Crystal glass

	LED	A	B	C
B50612	8.1 W	4 ⁵ / ₈	5 ¹ / ₄	78

Type:
 BEGA Product:
 Project:
 Modified:

