## Application

This GENIUS series pendant features a narrow beam distribution. An efficient hybrid optical system makes use of a silicone optical lens and precise reflector for maximum glare control.

## Materials

Clear safety glass Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Galvanized zinc-plated mounting bracket Pure anodized aluminum reflector surface Silicone optic with excellent high temperature and UV stability BEGA Hybrid Optics®

 $\ensuremath{\mathsf{NRTL}}$  listed to North American Standards, for interior use only

# Weight: 4.4 lbs.

## Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens	120-277V AC -30° C 11.5 W 14.0 W 0-10V, TRIAC, and ELV dimmable Ra > 90 1500 lm
LED service life (L70)	60000 hrs
LED service life (L/U)	60000 hrs

### LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

### Finish


Select the desired material finish by using appropriate code number as suffix.


## Available colors

White (.1)

Velvet black (.5)

Type: BEGA Product: Project: Modified:





Pendant luminaire ·	Narrow beam
---------------------	-------------

	LED		A	В	С
B50623	11.5W	15°	5 <sup>3</sup> / <sub>8</sub>	4 <sup>7</sup> / <sub>8</sub>	120

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 10/24/23