

Application

This compact luminaire is characterized by high light output and minimal recessed depth. The trimless, thick-walled crystal glass brings sparkle and added interest to any ceiling surface, while the inner frosted sections provide glare control.

Materials

Partially frosted pressed crystal glass
 Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Aluminum ceiling mounted driver box
 Pure anodized aluminum reflector surface
 Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 2.9 lbs.


Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	8.1 W
System wattage	12.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	809lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details



Semi-recessed downlight · Crystal glass

	LED	□	A	B
B50687	8.1 W	59°	5 ³ / ₄	3 ¹ / ₂

Type:

BEGA Product:

Project:

Modified:

Available options

CP50374 Ceiling pan (0–10V dimming only)

