Application

This compact luminaire is characterized by high light output and minimal recessed depth. The thick-walled crystal glass brings sparkle and added interest to any ceiling surface, while the inner frosted sections provide glare control.

Materials

Partially frosted pressed crystal glass

Marine grade, copper free (\leq 0.3% copper content) A360.0 aluminum alloy

Aluminum ceiling mounted driver box

Pure anodized aluminum reflector surface Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 5.3 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -20° C
LED module wattage 17.2 W
System wattage 21.0 W

Controllability 0-10V dimming down to 0.1%

Color rendering index Ra > 90 Luminaire lumens 1727 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available colors

White (.1) Stainless steel (.2)

Type:


BEGA Product:

Project: Modified:

Available options

CP50376 Ceiling pan (0-10V dimming only)





Semi-recessed downlight · Crystal glass					
	LED		А	В	
B50695	17.2 W	50°	8	43/4	