

Application

Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric narrow beam light distribution.

Materials

- Clear safety glass
- Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
- Molybdenum-bearing 316 grade stainless steel
- Stainless steel screw clamps
- High temperature silicone gasket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.3 lbs.

Electrical

LED module wattage	35.7 W
System wattage	42.0 W
Color rendering index	Ra > 90
Luminaire lumens	3530 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:


Modified:

Available options

FRO	Frosted lens
FSC	Fusing
HXL	Hex cell louver
SLL	Solite lens

Included (available for pre-shipment)

CP5929



Downlight · Narrow beam

	LED	□	A	B	C
B55829	35.7 W	14°	9 1/2	4 3/8	18

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com