Application

Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric narrow beam light distribution.

Materials

Clear safety glass Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket Stainless steel screw clamps Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations Protection class IP 65

12.7 W

15.5 W

Ra > 80

1076 lm 60000 hrs

Weight: 1.4 lbs.

Electrical

LED module wattage System wattage Color rendering index Luminaire lumens LED service life (L70)

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Silver (SLV) RAL: Bronze (BRZ) White (WHT) CUS: Type: BEGA Product: Project: Modified:

Included (available for pre-shipment) CP5925



•	C	;	·
• B	#	Ъ. Г	
	• A		

Downlight · Narrow beam								
	LED		А	В	С			
B55925	12.7 W	17°	5 ⁵ / ₈	31/4	18			

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 04/27/23