

**Application**

A compact ceiling mounted downlight with partially frosted crystal glass. The partially frosted crystal glass creates an additional vertical light component that supplements the downlight. These luminaires are designed for down lighting atriums, canopies, passages, and other interior and exterior locations.

**Materials**

Partially frosted pressed crystal glass  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 9.3 lbs.

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	35.7 W
System wattage	41.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	3283 lm
LED service life (L70)	60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

- |              |              |
|--------------|--------------|
| Black (BLK)  | Bronze (BRZ) |
| Silver (SLV) | White (WHT)  |
| RAL:         | CUS:         |

Type:


BEGA Product:

Project:

Modified:

**Available options**

- |     |                        |
|-----|------------------------|
| CUS | Custom finish          |
| FSC | Fusing                 |
| MGU | Marine grade undercoat |
| RAL | RAL finish             |



**Surface mounted downlight · Symmetric**

	LED	A	B
<b>B66058</b>	35.7 W	8 <sup>5</sup> / <sub>8</sub>	6 <sup>7</sup> / <sub>8</sub>

