Application

Surface mounted downlight with symmetric distribution. The patented (US 2016/0327243) BEGA Vortex Optics® rotates a parabolic reflector around the vertical axis to form a complex vortex shape. This vortex balances maximum efficiency with optimal glare control while eliminating shadows and artifacts in a uniquely square distribution..

Materials

Clear safety glass with optical texture

Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy Silicone applied robotically to casting, plasma treated for increased adhesion

Mechanically captive stainless steel fasteners

Fully potted waterstopper cable

BEGA Vortex Optics®

Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 3.5 lbs.

Electrical

Operating voltage 120-277V AC Minimum start temperature -30° C LED module wattage 17.8 W System wattage 20.0 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 80 Luminaire lumens 1378 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Surface mounted downlight \cdot Narrow beam

	LED		А	В	
B66155	17.8W	26°	51/8	4	

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

