

Application

Compact ceiling mounted downlight designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric distribution.

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.3 lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-40° C
LED module wattage	4.9W
System wattage	7.0W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	548 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 4000K (K4)
- 3500K (K35)
- 3500K (K35)
- 3000K (K3)
- 3000K (K3)
- 2700K (K27)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

ACD	Acrylic diffuser
CUS	Custom finish
FRO	Frosted lens
HXL	Hex cell louver
MGU	Marine grade undercoat
RAL	RAL finish
SLL	Solite lens

Available accessories

B19591	Remote driver box · Static white
--------	----------------------------------

See individual accessory spec sheet for details.

Included (available for pre-shipment)

B19538	Small opening wiring box
--------	--------------------------



Surface mounted downlight · Narrow beam • 24V DC

	LED	□	A	B
B66972	4.9W	29°	3 ³ / ₄	3 ¹ / ₂