

Application

Compact ceiling mounted downlight designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric distribution.

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.0 lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 10.0W
 System wattage 12.0W
 Controllability 0-10V, TRIAC, and ELV dimmable
 Color rendering index Ra > 80
 Luminaire lumens 954 lm
 LED service life (L70) 60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:

BEGA Product:

Project:

Modified:

Surface mounted downlight · Wide beam

	LED	□	A	B
B66982	10.0W	91°	5 ⁷ / ₈	5

