

Application

This compact LED ceiling mounted downlight is designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetrical narrow beam light distribution.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Clear safety glass
 Reflector made of pure anodized aluminum
 High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 6.6lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	35.7 W
System wattage	39.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	3499 lumens (3000K)
LED service life (L70)	60,000 hours

LED color temperature

- 4000K - Product number + **K4 (EXPRESS)**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3 (EXPRESS)**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



LED ceiling mounted downlight · narrow beam

	LED	β	A	B
66 983	35.7 W	16°	8 5/8	6 7/8

β = Beam angle

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
 © copyright BEGA 2018 Updated 03/20/19

Type:
 BEGA Product:
 Project:
 Modified:

