

Application

In-grade floodlight with symmetric light distribution. This family of luminaires is resistant to foot traffic and is ideally suited for the illumination of architectural details or landscape features around the home and garden. Low voltage magnetic transformer required for operation.

Materials

Clear safety glass
 Corrosion-resistant 304 grade stainless steel
 High temperature silicone gasket
 Composite installation housing
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 67

Weight: 1.9 lbs.

Electrical

Operating voltage	12VAC
Minimum start temperature	-40° C
LED module wattage	3.0W
System wattage	4.5W
Controllability	Non-Dimming
Color rendering index	Ra > 90
Luminaire lumens	320lm
LED service life (L70)	60000hrs


LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.



Garden floodlight · Symmetric · 12V AC

	LED	A	B	C
B77010	3.0W	4 ³ / ₈	2 ³ / ₄	4 ⁷ / ₈

Type:
 BEGA Product:
 Project:
 Modified:

Available accessories

B536 Low voltage magnetic transformer · 300W

See individual accessory spec sheet for details.

