Application

In-grade luminaire to illuminate ground surfaces. Equipped with two 90° light apertures to create a visual boundary on the edge of a pathway. These luminaires affix to a recessed BEGA junction box, supplied with luminaire, eliminating the need for deep recessed housings.

Materials

Borosilicate glass

Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Pure anodized aluminum reflector

 $\mbox{\bf NRTL}$ listed to North American Standards, suitable for wet locations Protection class IP 67

Weight: 2.1 lbs.

Electrical

LED module wattage 1.3 W
System wattage 1.5 W
Color rendering index
Luminaire lumens 10 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

 Black (BLK)
 Bronze (BRZ)

 Silver (SLV)
 White (WHT)

 RAL:
 CUS:

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

Available accessories

B19580 Remote driver box · Static white B19591 Remote driver box · Static white See individual accessory spec sheet for details.

Included (available for pre-shipment)

BB7069LED Installation housing



Ground-mounted luminaire · Twin 90° ports • 24V DC

	LED	Α	В	С
B77069	1.3W	61/,	11/2	13/4

