

**Application**

In-grade symmetric floodlight luminaires. These luminaires are designed to bear pressure loads of up to 4400lbs from vehicles with pneumatic tires. The luminaires must not be used for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating and changing direction.

**Materials**

- Clear safety glass
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 68

**Weight:** 1.8 lbs.

**Electrical**

LED module wattage	1.2W
System wattage	2.0W
Color rendering index	Ra > 80
Luminaire lumens	134 lm
LED service life (L70)	60000 hrs


**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

#4 brushed stainless steel. Custom colors are not available.



**In-grade luminaire · Symmetric • 24V DC**

	LED	□	A	B	C
<b>B77117</b>	1.2W	38°	3	1 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>2</sub>

Type:

BEGA Product:

Project:

Modified:

**Available accessories**

- B19580 Remote driver box · Static white
- B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

