

Application

Pole top luminaire with symmetric light distribution. The edge-lit source ensures visual comfort, while the unique interreflection of light in the clear diffuser creates visual interest. Ideal for illuminating pedestrian spaces such as plazas and building entrances.

Materials

Clear UV-stabilized acrylic diffuser
 Optically textured UV-stabilized acrylic diffuser
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 13.2lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 16.8W
 System wattage 19.0W
 Controllability 0-10V, TRIAC, and ELV dimmable
 Color rendering index Ra > 80
 Luminaire lumens 1401 lm
 LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:



Edge-lit pole-top luminaire · Symmetric

	LED	A	B
B77124	16.8W	15 ³ / ₈	19 ³ / ₈

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL finish

