

**Application**

Pole-top luminaire with symmetric light distribution. Ideal for illuminating squares, plazas and other open areas while adding visual interest.

**Materials**

Clear UV-stabilized acrylic diffuser  
 Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 11.0 lbs.

**EPA (Effective projection area):** 1.1 sq. ft.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature  $-30^{\circ}\text{C}$   
 LED module wattage 31.0W  
 System wattage 36.0W  
 Controllability 0-10V dimmable  
 Color rendering index  $Ra > 80$   
 Luminaire lumens 3370 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
DALI	Digital addressable lighting interface
MGU	Marine grade undercoat
RAL	RAL finish



**Pole-top luminaire · Symmetric**

	LED	A	B
<b>B77175</b>	31.0W	6 <sup>5</sup> / <sub>8</sub>	25 <sup>3</sup> / <sub>4</sub>

