

Application

Pole-top luminaire with adjustable, indirect light distribution. A symmetric distribution is produced when the top reflector is set in the horizontal position and becomes asymmetric when the reflector is adjusted from 0° to 30°. Not compatible with fixed base poles. Requires a hinged, 5" base diameter pole to install driver box. A high EPA pole is required to support this luminaire.

Materials

Clear safety glass
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 44.0 lbs.

EPA (Effective projection area): 6.0 sq. ft.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -40° C
 LED module wattage 55.3W
 System wattage 64.5W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 4320 lm
 LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:



Indirect pole-top luminaire · Adjustable

	LED	A	B
B77210	55.3W	38 ³ / ₄	23 ¹ / ₂

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 MGU Marine grade undercoat
 RAL RAL finish

