Application

Pathway luminaire with shielded light for use in the private sector. These luminaires are ideally suited for gardens, entryways, and for many applications on paths and terraces. Hardscape base is intended for installation on foundations or paved surfaces. Low voltage magnetic transformer required for operation.

Materials

Clear safety glass with matte finish Aluminum housing

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 6.3 lbs.

Electrical

Operating voltage 12VAC
Minimum start temperature -40° C
LED module wattage 2.1 W
System wattage 3.4 W
Controllability Non-Di

Controllability

Color rendering index

Luminaire lumens

LED service life (L70)

Non-Dimming

Ra > 90

131 lm

60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Garden bollard · Hardscape base • 12V AC

	LED	Α	В	С
B77264	2.1 W	43/8	271/2	43/8

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

MGU Marine grade undercoat

RAL RAL finish

Available accessories

B536 Low voltage magnetic transformer · 300W

See individual accessory spec sheet for details.

