

Application

Twin head bollard with shielded, direct light for illuminating entrances, paths, and many areas of public and private spaces. These luminaires provide glare-free illumination with a high degree of visual comfort for uniform lighting of ground surfaces.

Materials

Optically textured UV-stabilized acrylic diffuser  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Zinc plated carbon steel anchor bolts with template

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 13.7 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
Maximum ambient temperature	90° C
LED module wattage	15.2 W
System wattage	22.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1248 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:  
BEGA Product:  
Project:  
Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

B79817	Anchorage kit
--------	---------------



Bollard · Shielded · Twin

	LED	A	B	C
B77321	15.2 W	7 1/2	39 1/2	18 5/8