# Application

Compact rectangular floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architecture, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

#### Materials

Clear safety glass with optical texture

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket

Mechanically captive stainless steel fasteners 316 stainless steel 1/2" IPS threaded nipple

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 8.2 lbs.

EPA (Effective projection area): 0.4 sq. ft.

# Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 65.5 W
System wattage 76.0 W

Controllability 0-10V dimmable
Color rendering index Ra > 90
Luminaire lumens 6353 lm

LED service life (L70) 60000 hrs

# LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

### Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

# Type:

**BEGA Product:** 

Project: Modified:

# Available options

B70525 Glare shield · 180° CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

#### Available accessories

B19593 B19594	Surface mount conduit wiring box Direct burial wiring box
B70204	Earth spike
B70249	Pole cap · 3" O.D. pole tenon
B70252	Wood screw
B70280	Tube clamp
B70283	Screw clamp
B70379	Pole mount arm
B71042	Pole coupler
B79511	Mounting block

See individual accessory spec sheet for details.





