Application
Compact rectangular floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architecture, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials
Clear safety glass with optical texture
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
316 stainless steel 1/2" IPS threaded nipple
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.9 lbs.

EPA (Effective projection area): 0.2 sq. ft.

Electrical
Operating voltage	120, 220-240 OR 277 VAC
Minimum start temperature	-30° C
LED module wattage	17.9 W
System wattage	20.4 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2456 lm
LED service life (L70)	60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
B548	Barn door shield
B70500	Glare shield · 180°
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

Available accessories
B19593	Surface mount conduit wiring box
B19594	Direct burial wiring box
B70204	Earth spike
B70249	Pole cap · 3" O.D. pole tenon
B70252	Wood screw
B70280	Tube clamp
B70283	Screw clamp
B70379	Pole mount arm
B71042	Pole coupler
B79511	Mounting block

See individual accessory spec sheet for details.

Floodlight · Wide beam

	LED	□	A	B	C
B77479	17.9 W	74°x89°	6¹/₂	7	3¹/₂