

Application

Compact rectangular floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architecture, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

Clear safety glass with optical texture
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 3.3 lbs.

EPA (Effective projection area): 0.3 sq. ft.

Electrical

Operating voltage 120, 220-240 OR 277 VAC
 Minimum start temperature -30° C
 LED module wattage 17.9W
 System wattage 20.4W
 Controllability 0-10V dimmable
 Color rendering index Ra > 90
 Luminaire lumens 2268 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- B548 Barn door shield
- B70500 Glare shield · 180°
- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish



Floodlight · Linear spread

	LED	□	A	B	C	D
B77536	17.9W	26°x89°	6 1/2	7 1/4	3 1/2	4

