

Application

Compact rectangular floodlight with mounting canopy and outrigger arm. Designed to illuminate architecture and signage. Pair with a variety of optical accessories.

Materials

Clear safety glass with optical texture
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 304 stainless steel outrigger arm
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 7.7 lbs.

EPA (Effective projection area): 0.6 sq. ft.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -30° C
 LED module wattage 39.0W
 System wattage 42.8W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 3097 lm
 LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:



Floodlight · Wide beam

	LED	□	A	B	C	D
B77559	39.0W	82°x96°	9	27 ⁵ / ₈	2 ¹ / ₄	9 ³ / ₈

Type:

BEGA Product:

Project:

Modified:

Available options

B549 Barn door shield
 B70502 Glare shield · 180°
 CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL finish

