Application

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

Pure anodized aluminum reflector

Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 2.0 lbs.

Electrical

Operating voltage 24VDC (remote power supply reg.)

Minimum start temperature -40° C LED module wattage 7.9W System wattage 9.0W

Non-Dimming Controllability Color rendering index Ra > 80 Luminaire lumens 888 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ) White (WHT) Silver (SLV) RAL: CUS:

Type:

BEGA Product:

Project: Modified:

Available options

AMB Amber LED

B70050 Elliptical spread lens B70755 Glare shield · 180° CUS Custom finish MGU Marine grade undercoat

RAL RAL finish

Available accessories

B19580 Remote driver box · Static white B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

Small opening wiring box B19538





Compact floodlight · Wide beam • 24V DC

D LED B77607 7.9W 31/,