

**Application**

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

**Materials**

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector
- Silicone optic with excellent high temperature and UV stability
- Composite concentric ring louver

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 5.1 lbs.

**EPA (Effective projection area):** 0.3 sq. ft.

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	12.5W
System wattage	15.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	1132lm
LED service life (L70)	60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

- |              |              |
|--------------|--------------|
| Black (BLK)  | Bronze (BRZ) |
| Silver (SLV) | White (WHT)  |
| RAL:         | CUS:         |

Type:


BEGA Product:

Project:

Modified:

**Available options**

- |        |                        |
|--------|------------------------|
| B70076 | Elliptical spread lens |
| B70720 | Glare shield · 360°    |
| B70757 | Glare shield · 180°    |
| CUS    | Custom finish          |
| MGU    | Marine grade undercoat |
| RAL    | RAL finish             |



**Compact floodlight · Very narrow beam**

	LED	□	A	B	C	D
<b>B77700</b>	12.5W	9°	6 1/4	8 7/8	6 1/2	3 7/8

