Application

Compact floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

Clear safety glass

Marine grade, copper free (${\leq}\,0.3\%$ copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

316 stainless steel 1/2" IPS threaded nipple

Pure anodized aluminum reflector

Silicone optic with excellent high temperature and UV stability

 $\ensuremath{\mathsf{NRTL}}$ listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 4.6 lbs.

EPA (Effective projection area): 0.3 sq. ft.

Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens LED service life (L70)

120-277V AC -30° C 19.2 W 22.0 W 0-10V, TRIAC, and ELV dimmable Ra > 90 1851 Im 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Silver (SLV) RAL: Bronze (BRZ) White (WHT) CUS: Type: BEGA Product: Project: Modified:


Available options

B70060	Elliptical spread lens
B70720	Glare shield · 360°
B70757 Glare	Э
shield · 180°	
B70796	Concentric ring louver
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

Available accessories

B19593 B19594	Surface mount conduit wiring box Direct burial wiring box
B70204	Earth spike
B70249	Pole cap · 3" O.D. pole tenon
B70252	Wood screw
B70280	Tube clamp
B70283	Screw clamp
B70379	Pole mount arm
B71042	Pole coupler
B79511	Mounting block

See individual accessory spec sheet for details.



Compact floodlight · Narrow beam								
	LED		А	В	С			
B77704	19.2W	26°	61/4	81/2	6 ¹ / ₂			

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 05/03/23