

Application

Bollard luminaire with unshielded 360° light distribution. Provided without safety guard and three-ply opal glass for even illumination. Designed for use in the illumination of gardens and residential installations.

Materials

Hand-blown three-ply opal glass
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 5.7 lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 Maximum ambient temperature 90° C
 LED module wattage 3.9W
 System wattage 10.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 90
 Luminaire lumens 441 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish



Bollard · Unshielded			
	LED	A	B
B77742	3.9W	4 ³ / ₈	28 ³ / ₄

