## Application

The unshielded light of this luminaire is ideally suited for structuring and dividing open spaces. The construction is robust enough for people to sit or stand on. BEGA light design elements are like luminous sculptures, ideal for sophisticated arrangements of open spaces, along pathways and on roof terraces.

# Materials

White UV-stabilized acrylic diffuser Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy Mechanically captive stainless steel fasteners Galvanized steel anchorage

**NRTL** listed to North American Standards, suitable for wet locations Protection class IP 65

# Weight: 43.4 lbs.

# Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens LED service life (L70) 120-277V AC -30° C 16.8 W 21.0 W 0-10V dimmable Ra > 80 859 Im 60000 hrs

# LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

# Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

### Available colors

Black (BLK) Silver (SLV) RAL: Bronze (BRZ) White (WHT) CUS: Type: BEGA Product: Project: Modified:

### Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

### Included (available for pre-shipment) B79812 Anchorage kit

LED A **B77764** 16.8W 15<sup>3</sup>/<sub>4</sub>

Urban furniture · Unshielded bollard

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

В

18

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com

