

Application

Twin pole-top luminaire with asymmetric wide beam light distribution designed to illuminate roadways, squares, driveways and pedestrian areas. Tool-less entry for ease of maintenance. Provided with slip fitter to fit 3" O.D. poles.

Materials

Optically textured UV-stabilized acrylic diffuser
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Mechanically captive stainless steel fasteners
 High temperature silicone gasket
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 66

Weight: 31.0lbs.

EPA (Effective projection area): 1.5 sq. ft.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 46.4 W
 System wattage 62.2 W
 Controllability 0-10V, TRIAC, and ELV dimmable
 Color rendering index Ra > 80
 Luminaire lumens 3627 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish



Pole-top luminaire · Asymmetric wide beam · Twin

	LED	A	B	C
B77839	46.4 W	55	15 ³ / ₈	5 ³ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com