#### Application

Ideal as individual luminaires for marking egress and danger areas or in rows for illuminating corridors or passageways in public and private projects.

#### Materials

Pressed crystal glass with white ceramic coating on one side Marine grade, copper free ( $\leq$  0.3% copper content) A360.0 aluminum alloy

120-277VAC

Non-Dimming

-20° C

3.3W

4.9W

Ra > 90 164 lm

60000 hrs

NRTL listed to North American Standards, for interior use only

## Weight: 0.9 lbs.

# Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens LED service life (L70)

### LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

 ${\rm BEGA}$  can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

### Finish

Select the desired material finish by using appropriate code number as suffix.


## Available colors

White (.1) Chrome (.3) Stainless steel (.2)

Type: BEGA Product: Project: Modified:

Included (available for pre-shipment) B19538 Small opening wiring box





• A • • C •

Wall luminaire · Crystal glass					
		LED	А	В	С
B78047	ADA	3.3W	31/2	4	2 <sup>1</sup> / <sub>8</sub>

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 05/09/23