

**Application**

Bollard luminaire with unshielded 180° light distribution and safety guard designed for use in the illumination of gardens and residential installations. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

**Materials**

Hand-blown three-ply opal glass  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Mechanically captive stainless steel fasteners  
 High temperature silicone gasket  
 Zinc plated carbon steel anchor bolts with template

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 13.3lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature -30° C  
 Maximum ambient temperature 90° C  
 LED module wattage 5.8W  
 System wattage 11.0W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 180lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

**Included (available for pre-shipment)**

B79817	Anchorage kit
--------	---------------



**Bollard · Unshielded with safety guard · 180°**

	LED	A	B
<b>B84025</b>	5.8W	5 1/8	35 3/4

