

**Application**

Pole-top luminaire with partially shielded light distribution. A combination of materials in perfect harmony with this classic luminaire shape.

**Materials**

Hand-blown three-ply opal glass  
 99.9% pure copper  
 High-strength, free machining C38500 brass

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 8.8 lbs.

**Electrical**

|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277VAC     |
| Minimum start temperature | -30° C         |
| LED module wattage        | 6.4 W          |
| System wattage            | 8.0 W          |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 368 lm         |
| LED service life (L70)    | 60000 hrs      |

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**


Natural cast bronze and copper. Time and weather factors will create the natural patina of bronze and copper.

Type:

BEGA Product:

Project:

Modified:



**Cast bronze and copper pole-top luminaire · Unshielded**

|               | LED   | A                              | B                              |
|---------------|-------|--------------------------------|--------------------------------|
| <b>B84045</b> | 6.4 W | 13 <sup>3</sup> / <sub>4</sub> | 16 <sup>1</sup> / <sub>8</sub> |

