

Application

Light building element with symmetric light distribution designed for direct burial installation. Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Materials

Clear safety glass
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Anchorage must be buried
 Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 94.8lbs.

EPA (Effective projection area): 9.0 sq. ft.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 39.0W
 System wattage 48.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 2416lm
 LED service life (L70) 60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Building element · Symmetric

	LED	A	B	C	D
B84064	39.0W	8 ⁵ / ₈	81 ³ / ₈	177	31 ¹ / ₂

Type:

BEGA Product:

Project:

Modified:

Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish

