

Application

Twin pole-top luminaire with asymmetric wide beam light distribution. Designed to illuminate roadways, squares, driveways and pedestrian areas while meeting full cutoff requirements.

Materials

Clear safety glass
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 66

Weight: 34.2 lbs.

EPA (Effective projection area): 1.3 sq. ft.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -30° C
 LED module wattage 31.6W
 System wattage 40.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 4320 lm
 LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:



Pole-top luminaire · Asymmetric wide beam · Twin

	LED	A	B	C
B84123	31.6W	11 1/2	4 1/4	47 3/4

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 DALI-2 Digital addressable lighting interface
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL finish

