

Application

Light building elements are luminous design features for public areas. These luminaires are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances, and atria. DarkSky Approved (2700K and 3000K only).

Materials

Optically textured UV-stabilized acrylic diffuser
 Die-cast aluminum
 Extruded aluminum pole shaft
 High temperature silicone gasket
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 54.0lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 19.5W
 System wattage 24.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 2358lm
 LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3) (DarkSky Approved)
 2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL finish



Building element · Asymmetric

	LED	A	B	C	D
B84138	19.5W	5 1/4	19 1/4	157 1/2	31 1/2

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com