

**Application**

With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate large parking areas and plazas. Provided with slip fitter to fit 3" O.D. poles.

**Materials**

Optically textured UV-stabilized acrylic diffuser  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 61.7 lbs.

**EPA (Effective projection area):** 1.6 sq. ft.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -30° C  
 LED module wattage 46.4 W  
 System wattage 52.0 W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 4734 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



**Edge-lit pole-top luminaire · Symmetric**

	LED	A	B
<b>B84147</b>	46.4 W	29 1/2	32 3/8

Type:

BEGA Product:

Project:

Modified:

**Available options**

- CUS Custom finish
- DALI Digital addressable lighting interface
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish

