### Application

Compact performance floodlight with mounting canopy for mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, landscaping, signage, and for general illumination of a space. Pair with a variety of optical accessories.

## Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Mechanically captive stainless steel fasteners High temperature silicone gasket Pure anodized aluminum reflector surface Silicone optic with excellent high temperature and UV stability

BEGA Hybrid Optics®

 $\ensuremath{\textbf{NRTL}}$  listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 10.1 lbs.

EPA (Effective projection area): 0.43 sq. ft.

# Electrical

Operating voltage Minimum start temperature LED module wattage System wattage Controllability Color rendering index Luminaire lumens LED service life (L70)

120-277V AC -40° C 60.3 W 69.0 W 0-10V dimmable Ra > 90 6952 Im 60000 hrs

#### LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

#### Available colors

Black (BLK)	
Silver (SLV)	
RAL:	

Bronze (BRZ) White (WHT) CUS: Type: BEGA Product: Project: Modified:

### Available options

B71123	Elliptical Spread Lens
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

### Available accessories

B71121	Glare shield · 180°
B79831	Glare shield · 360°

See individual accessory spec sheet for details.



Performance floodlights · Wide beam								
	LED		А	В	С	D		
B84224	60.3 W	54°	8 <sup>1</sup> / <sub>4</sub>	12 <sup>3</sup> / <sub>8</sub>	5 <sup>1</sup> / <sub>4</sub>	5 <sup>1</sup> / <sub>8</sub>		

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com © copyright BEGA 2024 Updated 12/29/23

