

**Application**

Light building element with asymmetric light distribution. Light building elements are luminous design features for public areas. They are usually suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

**Materials**

Clear safety glass with optical texture  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Extruded aluminum pole shaft  
 High temperature silicone gasket  
 Galvanized steel anchorage  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 72.8 lbs.

**EPA (Effective projection area):** 9.7 sq. ft.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -20° C  
 LED module wattage 17.6W  
 System wattage 22.0W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 90  
 Luminaire lumens 2521 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:


Modified:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

**Included (available for pre-shipment)**

B79802 Buried anchorage kit



**Building element · Asymmetric · Single**

	LED	A	B	C
<b>B84274</b>	17.6W	9 1/4	11	137 3/4