

Application

Surface washer bollards for the uniform illumination of ground surfaces. The luminaire housing is adjustable, allowing the light distribution to be adapted to meet the requirements of the installation site.

Materials

- Clear safety glass with printed optical texture
- Aluminum housing
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 15.4 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	13.6 W
System wattage	24.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	2109 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Bollard · Flat beam

	LED	A	B	C
B84304	13.6 W	10 ¹ / ₄	47 ¹ / ₈	14

Type:
BEGA Product:
Project:
Modified:

Available options

70895	Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

B79817	Anchorage kit
--------	---------------

