

Application

A large-scale, high-output floodlight with mounting yoke designed to illuminate bridges, monuments, building facades or large signage. For use in ambient temperatures that do not exceed 25° C.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel mounting yoke
- Pure anodized aluminum reflector surface
- Composite concentric ring louver
- BEGA Hybrid Optics®
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 23.8 lbs.

EPA (Effective projection area): 1.3 sq. ft.

Electrical

| | |
|-----------------------------|----------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -40° C |
| Maximum ambient temperature | 25° C |
| LED module wattage | 97.2W |
| System wattage | 122.0W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 4117 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

| | |
|--------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| RAL: | CUS: |



High-performance floodlight · Very narrow beam

| | LED | □ | A | B | C |
|---------------|-------|------|--------------------------------|----|-------------------------------|
| B84328 | 97.2W | 4.8° | 14 ³ / ₄ | 16 | 6 ⁷ / ₈ |

Type:

BEGA Product:

Project:

Modified:

Available options

| | |
|--------|--------------------------|
| B71110 | Glare shield · 180° |
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| RAL | RAL finish |
| VRV | Vibration resisting yoke |

Available accessories

| | |
|--------|----------------------------|
| B70761 | Cross beam · 3 floodlights |
| B70762 | Pole cap · 2 floodlights |
| B70763 | Pole cap · 3 floodlights |
| B70764 | Pole cap · 4 floodlights |
| B70765 | Cross beam · 6 floodlights |
| B79550 | Pole mount arm |
| B79551 | Wall mount arm |
| B79555 | Pole-top mounting hub |

See individual accessory spec sheet for details.

